

# sewoo

## 3-Inch POS Printer

# SLK-TS100




- High Performance Easy Maintenance
- Ergonomic Design Entry-level Printer
- Easy maintenance with Jam release lever
- Simple and easy replacement of components including head, motor, cutter, PCB, etc
- Easy maintenance for paper jam
- Ideal for top exit printing with wall mount
- High speed printing at 8.6ips (220mm/sec)



Barcode



Durable



Paper Width



Easy Loading



Fast Speed



Compact Design



Easy Maintenance

## APPLICATION



## SPECIFICATIONS



### PRINTER CHARACTERISTICS

#### Print Method

Direct thermal

#### Print Speed

220mm/sec

#### Print width

2.83"  
(72mm, adjustable by commands)

#### Resolution

203 dpi

#### Power

Power type : External SMPS

AC : 110~220Vac 50/60Hz

DC : 24Vdc / 2.5A

#### Sensor

Paper end, Cover open

#### Reliability

TPH life : 100km

MCBF : 80 Million lines

Cutter life : 1.5 Million cuts

#### Drawer port

circuit (24V, Max. 1A)



### PHYSICAL CHARACTERISTICS

#### Dimension (W x D x H)

5.59" x 7.28" x 5.35"  
(142 x 185 x 136mm)

#### Weight

2.25b(1.02Kg)



### INTERFACES

1. USB+SEIRAL(RS-232C\_9pin)+RJ45 serial+Ethernet Built-in
2. USB+SEIRAL(RS-232C\_9pin)+RJ45 serial (korea standard)



### CERTIFICATIONS

CE, FCC, KC,ENERGY STAR,  
ROHS



### OPERATING CHARACTERISTICS

#### Operating Temperature

32 ~ 113°F(0 ~ 45°C)

#### Operating Humidity

10 ~ 80RH%

#### Storage Temperature

14 ~ 140°F(-10 ~ 60°C)

#### Storage Humidity

10 ~ 90RH%



### MEDIA CHARACTERISTICS

#### Media Type

Thermal receipt paper

#### Media Width

79.5±0.5mm

#### Media Core Diameter

0.49 ~ 0.5"(12.5mm ± 0.5mm)

#### Media Roll Diameter

3.1"(Max. ø 80mm)

#### Thickness

0.06~0.08mm



### SOFTWARE

#### Emulations

ESC/POS Command compatible

#### Drivers

Windows Driver(XP ~, Server2003 ~),

Linux Driver, Mac Driver, OPOS Driver,

JavaPOS Driver

#### SDK

Android(6.0 ~) SDK, Windows SDK



### BARCODES

#### 1D

EAN-8, EAN-13, Code 39,

Code 93, Code 128, ITF,

UPC-A, UPC-E, Codabar

#### 2D

PDF 417, QR code



### FONTS / GRAPHICS

#### Character Type

Font A(12x24), Font B(9x17),

Chinese(Traditional/Simplified, 24x24),

Korean(24x24), Japanese(24x24)

#### Characters per line (CPL)

Font A(12x24) : 48cpl or 42cpl,

Font B(9x17) : 64cpl or 56cpl

Chinese/Korean/Japanese: 24cpl

#### Character set

95 Alphanumeric,

16 International,

128 x 18 Graphic



### ACCESSORIES

#### Built in melody standard

1. SLK-TS100E(USB + Serial + Ethernet)

: Built in melody

2. Korea standard

(USB+SEIRAL(RS-232C\_9pin)+RJ45 serial)

: Built in melody

# sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprinter.com

www.miniprinter.com

USA, Inc.

Torrance, CA 90502, USA

T. +1-310-617-7401

E. NA\_Sales@miniprinter.com

México

Cuauhtémoc, Mexico D.F.

T. +52-1-55-3232-9543 M. +52-1-55-143893

E. LA\_Sales@miniprinter.com

