







Lifting Assembly

SLM-DJ3010-A

Simple Configuration, Anti Off-Center Ability



Effortless Installation, Simple Configuration

Seamlessly integrate with AMB-300XS using just 4 bolts. Quick-connect to the chassis' reserved connectors. Roboshop ensures rapid configuration with unparalleled ease of use.



Customizable Lifting Height

Tailor the lifting height based on the actual scenario. The supported lifting height ranges from 50 mm to 150 mm.



Enhanced Adaptability to Off-Center Loads

In width, the rated load capacity will not change no matter how the center of gravity shifts.

In length, the rated load capacity will decrease by no more than 33% when responding to shifts in the load's center of gravity.



Load Up to 300 kg

Lifting loads ranging from 0 kg to 300 kg, meeting material handling needs in diverse fields such as factory logistics, e-commerce, 3C electronics, and other scenarios.



Basic parameters

Product model	SLM-DJ3010-A
Product name	Lifting Assembly
LxWxH	820 x 560 x 103.5 mm (customizable)
Rated load capacity	300 kg
Lifting height	60 mm (customizable)
Lifting time	≤6 s
Shell material	SPCC
Shell color	RAL9003 Signal white (customizable)
Nominal weight	65 kg





Dimension

(mm)



