



Suitable for
AMB-300XS



Roller Assembly

SLM-DR1534-A

Quick Configuration, Out-of-the-box



Easy to Use

With just 6 bolts, it can be secured onto the AMB-300XS. Quickly plug into the reserved connectors, enabling Roboshop to achieve rapid setup, offering effortless user experience.



Customizable Docking Height

Tailor the docking height based on the actual scenario. The supported height ranges from 500 mm to 1500 mm.



Enhanced Security with Multi-protection

Designed with 3 sets of material detection photoelectric sensors, ensuring the safety and accuracy in the material transportation process.



Load Up to 150 kg

With a conveying weight range of 0 kg to 150 kg, it is designed to meet material handling needs in diverse fields such as e-commerce, shoes and clothing, medical, and 3C electronics.



Enhanced Flexibility with Adjustable Speed

Features a conveying speed range of 2.7 m/min to 27.7 m/min, capable of automatic adjustments to accommodate different operational rhythms.

Basic parameters

Product model	SLM-DR1534-A
Product name	Roller Assembly
L x W x H	820 x 560 x 343 mm (customizable)
Rated load capacity	150 kg
Roller conveying speed	2.7 m/min to 27.7 m/min
Number of rollers	6
Baffle lifting time	2 s
Suitable material dimension: L x W	≤600 x 400 (customizable)
Shell material	SPCC
Shell color	RAL9003 Signal white (customizable)
Nominal weight	66 kg



Dimension (mm)

